


Technical Specifications

DIA (mm)	COATING		1570 N/mm²		1770 N/mm²		1960 N/mm²	
0.20	Phosphated	Galvanized						
0.25	Phosphated	Galvanized					1960	Patented
0.30	Phosphated	Galvanized			1770	Patented	1960	Patented
0.35	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.40	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.45	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.50	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.55	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.60	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.65	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.70	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.75	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.80	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
0.90	Phosphated	Galvanized	1570	Patented	1770	Patented	1960	Patented
1.00	Phosphated	Galvanized	1570	Patented	1770	Patented - W/R	1960	Patented - W/R
1.10	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.20	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.30	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.40	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.50	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.60	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.70	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R
1.80	Phosphated	Galvanized	1570	Patented - W/R	1770	Patented - W/R	1960	Patented - W/R




BS60-METAL CABLE DRUM

2160 N/mm ²		PACKING				
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented	BS60 Reel	250 - 450 kg Z2			
2160	Patented		250 - 450 kg Z2			
2160	Patented		250 - 450 kg Z2			
2160	Patented		250 - 450 kg Z2			
2160	Patented - W/R		250 - 450 kg Z2			
2160	Patented - W/R		250 - 450 kg Z2			
2160	Patented - W/R		250 - 450 kg Z2			
2160	Patented - W/R					
2160	Patented - W/R					
2160	Patented - W/R					
2160	Patented - W/R			500 - 1000 kg Z3		
				500 - 1000 kg Z3		
				500 - 1000 kg Z3		



450 KG W=250-H=280 850 D=700d=356



0

W=500-1000 KG H=560 D=700-850 d=450

